



PLAN

SCALE 1:25

NOTES:

1. REINFORCEMENT STEEL TO BE MINIMUM 1 METRE LENGTH N12
2. MINIMUM OF 200mm PATH EITHER SIDE OF THE JUNCTION PIT COVER
3. CONCRETE COVER TO REINFORCEMENT STEEL TO BE MINIMUM 50mm
4. INCREASE THICKNESS OF FOOTPATH PANEL FOR 1 METRE EITHER SIDE OF THE JUNCTION PIT TO 150mm
5. SQUARE JUNCTION PIT LIDS PREFERRED IN ALL PATHS
6. CONTRACTION JOINTS TO USED IN THE INSTALLATION OF COVERS IN ALL PATHS

AMENDMENTS	REVISION	DATE	DESCRIPTION	BY	CHECKED	APPROVED
1	4/2/2015	LAYERS& DWG NO'S UPDATED	SA	MB	MB	

GENERAL NOTES  
 1. THIS DRAWINGS ALWAYS REMAINS THE PROPERTY OF THE CITY OF GOSNELLS AND MUST NOT BE RETAINED OR REPRODUCED WITHOUT PERMISSION  
 2. IN THE ABSENCE OF THE APPROVED SIGNATURE (ie MANAGER TECHNICAL SERVICES) THIS DRAWING SHALL BE TREATED AS PRELIMINARY  
 3. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS NOTED OTHERWISE

**CITY OF GOSNELLS**

2120 Albany Highway Gosnells 6110  
 PO Box 662, GOSNELLS 6990  
 WESTERN AUSTRALIA

Telephone 08 9397 3000  
 Facsimile 08 9397 3333  
 Online www.gosnells.wa.gov.au

STANDARD DRAWING		
JUNCTION PIT / FOOTPATH DETAIL		
DESIGN MB	DRAWN GL	DRAWING A4
SCALE 1:25	CHECKED AT	DATE 30/07/10

STANDARD DRAWING NUMBER	ES-19-10
MANAGER TECHNICAL SERVICES	M.BOTTE 4/2/15
	M. BOTTE